



Quality Tools for Smart Cleaning™

**HYDRO
POWER®** **RO**
SYSTEM



HYDRO POWER® RO
BOOST YOUR PURE WATER CLEANING



YOUR ECONOMICAL SOLUTION FOR CLEANING WITH PURE WATER IN HARD WATER AREAS

With the new **HydroPower RO**, cleaning with pure water can be achieved at minimal running cost – especially in hard water areas. Due to its compact and robust design, the new **HydroPower RO** system is easy to transport.

The proven RO-technology from **UNGER** relies on a 3-stage filtration process with 0 ppm outgoing pure water, and the water is pressurized by a high-quality stainless steel pump.

The boost function allows a strong tap water-jet on demand for prewashing heavy soiled or horizontal surfaces. It will also remove cobwebs and dirt from corners that cannot be reached with a brush.

Save money now and get your jobs done with the new **UNGER HydroPower RO**.



EASY AND SAFE USAGE

- TDS meter displays the quality of the outgoing water at the touch of a button
- Manual flushing of RO membrane for an extended lifetime
- Automatic shut-off function for protection of the pump in case the water supply stops



HIGH QUALITY 3-STAGE FILTRATION

1. Combi pre-filter to capture chlorine and sediments
2. Premium RO membrane to remove dissolved minerals
3. DI polisher to filter any remaining impurities = 100% pure water!

POWERFUL HIGH-VALUE PUMP

- Centrifugal pump for constant and high water flow
- Made of stainless steel
- Trouble-free operation even after long periods of non-use

EASY TO TRANSPORT

- Compact unit fits in most vehicles
- Easy to load, unload and maneuver
- Automatic water stop prevents leaking

HYDRO POWER[®] RO SYSTEM



BOOST MODE!

- Boost mode: 108 gal./h (409L/h) of tap water with 116-145 PSI (8-10 bar) for prewashing of heavy-soiled surfaces
- Pure water mode: up to 60 gal./h (227L/h) of pure water with 58 PSI (4 bar) for spotless cleaning of windows and facades


EASY TO MAINTAIN

- Pre-filter and DI polisher are easy to change and can be visually controlled during work
- Removable back cover for easy access to all electric components

COMPACT AND ROBUST DESIGN

- Made of premium quality materials – long service life
- Durable stainless metal quick-release connectors, designed to eliminate leaks or drips
- Heavy duty stainless steel frame with maintenance free solid rubber wheels

DLH25 – DURAFLEX HIGH PERFORMANCE HOSE*



- Durable high performance quick connect hose for pure water supply from water filter to brush
- For use with RO System Only (R020S)
- Diameter: 10mm outer / 7 mm inner

**Sold separately from unit*



HYDRO POWER[®] RO SYSTEM

	HydroPower [®] RO
Part No.	R020S
Water output up to*	Boost mode: Up to 108 gal./h (409 l/h) Pure Water mode: Up to 60 gal./h (227 l/h)
Water outlets	1
Pump performance	0.50 HP
Electrical Specifications	Connection: 110V / 60Hz Consumption: 0.37 kW Min. Voltage: 104V / 60Hz
Protection class	Electric motor: IP 44 Pump Control: IP 65
Inlet pressure	14-87 PSI (1-6 Bar)
Max. operating pressure	145 PSI (10 Bar)
Pump dry run protection	✓
Water flow meter	Analog
Pre-filter	Combi filter Chlorine/Sediments (ROCFC)
Membrane	Membrane Unit (ROMEM) Maintenance Liquid (ROMML)
Resin filter	Resin Catridge (RORFC)
TDS sensors	At water outlet
Compact Design	38" L × 21" W × 18" H
Tare weight	99 lbs.
Weight incl. filling	110 lbs.
Power Cord Length	20' / 6m

*Flow rate will vary depending on factors such as water temp, PSI level, accessories used.



Scan here for more
information

